BPX							
CIBSE TM65.2 En	nbodied Carbon Mi	id-level Calculation					
Date:		11/10/2023					
Assessor/Organisa Contact:		Stoane Lighting sales@mikestoanelightin	ig.com				
Embodied Carbon	Populto with 'Mid Lo	evel TM65 Calculation' M	othod Total				
Embodied Carbon				kg CO2e			
Through Life (25 y	ear) Embodied Carl	bon (kqCO₂e)	0.01				
	First Build	() - 2 /	Re	pair			
	7.98 0.38						
1 2 3	4 5 6	7 8 9 10 1	11 12 13 14 1	5 16 17 18	19 20 21 2	2 23 24 25	
25 year product life	e						
Product Informati	on						
Type of Product Product Weight						Luminaires 0.400 kg	
Material Breakdow		f the product weight. Bre	eakdown			100.00%	
	ced as part of repai on of the factory pe					0.382 kgCO2e 4.14 kWh	
Location of Manufa		•				burgh, Edinburgh, City	
Product Complexity	/					of, United Kingdom Category 2	
			Materials by % of Pro	oduct Weight			
100% —			Materials by % of Pro	oduct Weight			
100% — 90% —			Materials by % of Pro	oduct Weight			
			Materials by % of Pro	oduct Weight			
90% —			Materials by % of Pro	oduct Weight	67.76%		
90% — 80% —			Materials by % of Pro	oduct Weight	67.76%		
90%			Materials by % of Pro	oduct Weight	67.76%		
90%			Materials by % of Pro	oduct Weight	67.76%	29.04%	
90%			Materials by % of Pro	oduct Weight	67.76%	29.04%	
90%			Materials by % of Pro	oduct Weight	67.76%	29.04%	
90%	0.75%	1.23%	Materials by % of Pro	0.78%	67.76%	29.04%	
90%	0.75% Copper	1.23% Plastics (general)				29.04%	
90%			0.45% Printed circuit board	0.78%	Aluminium Ingot fro		
90%			0.45% Printed circuit board	0.78%	Aluminium Ingot fro		
90%			0.45% Printed circuit board	0.78%	Aluminium Ingot fro		
90%			0.45% Printed circuit board	0.78%	Aluminium Ingot fro		
90%			0.45% Printed circuit board	0.78%	Aluminium Ingot fro		
90%			0.45% Printed circuit board	0.78%	Aluminium Ingot fro		

STOANE LIGHTING

EQUIPMENT DESIGN + MANUFACTURE

TM65.2 Lighting Calculation: Luminaire

врх

CIBSE TM65 Embodied Carbon Mid-level Calculation

Embodied Carbon Results Breakdown (kg CO ₂ e)	
A1: Material Extraction	2.422
A2: Transport	0.158
A3: Manufacturing	2.359
A4: Transport to Site	0.016
B3: Repair	0.294
C2: Transport	0.005
C3: Waste Processing	1.179
C4: Disposal	0.002
Embodied Carbon Results (kg CO ₂ e)	
A1-C4	6.44
A1-C4 with Buffer Factor	8.37
Assumptions	
A1: Material carbon coefficient source	TM65, Table 2.1; TM65.2 Table 9
C4 Percentage of product going to landfill(%)	55% - TM65 Table 4.14

This report was generated using the CIBSE TM65 Manufacturers form 'beta' version V1.3. Released in August 2023

Stoane Lighting are a UK based company.

Files are generated for a 'standard' version of the fitting and may not include calculations for accessories or derivatives. Only if LED drivers or Power supplies are integral will they be included in the calculation. Repair embodied carbon is calcualted based on light source and control gear replacement once in the 25 year product life

For more inoformation please contact us via our website shown below.



This report was produced using the CIBSE documents; TM65 Embodied Carbon of MEP Products - June 2021 TM65.2 Lighting - August 2023

www.stoanelighting.com